



高新技术企业/专精特新企业
专业的高温加热制造工厂 (-100~2600°C)

中国热处理行业协会理事单位
ISO45001:职业健康管理体系认证
ISO14001:环境管理体系认证
ISO9001:质量管理体系认证
欧盟CE产品认证



24h
咨询电话
13271526781
+86 379-69936789



Model type	GWL-1200XL
Furnace chamber dimensions (mm) furnace chamber	L=1100, W=600, H=250; L=1300, W=800, H=400
External dimensions (mm) Dimensions	See the drawing for details
AC power supply maximum	380V; 50HZ
operating temperature Maximum service temperature	1200 degrees1200 degrees
Long-term operating temperature Can be used for a long time temperature	 1150 degrees 1150 Degrees Main

Website: www.gwdl.com Email : wgq@gwdl.com Contact Information: 13271526781 0379-69936789 Address : No. 1, Xingye 1st Road, Science and Technology Industrial Park, Jianxi District, Luoyang City , Henan Province



高新技术企业/专精特新企业
专业的高温加热制造工厂 (-100~2600°C)

中国热处理行业协会理事单位
ISO45001:职业健康管理体系认证
ISO14001:环境管理体系认证
ISO9001:质量管理体系认证
欧盟CE产品认证




咨询电话 
13271526781
+86 379-69936789

Feel
my
connection

you
in

Gongluo Kiln

Thank you for
establishing
contact with us!
Thank
to get
touch
With us!
Company
Name:
Yangjuxing
Furnace Co., Ltd.

The control range is Control range is	100 to 1200 degrees
Temperature sensing element temperatu re measurer	Thermocouple type K, temperature measurement range 0-1320 degrees Celsius ThermocoupleindexnumberK,temperaturerange0- 1320degrees
Heating element heater element	High-temperature alloy resistance wire High temperature alloy resistance wire
Heating element mounting position Location of Heating element	 Three-sided heating, with additional heating on both sides and bottom. Heat on three sides, add the bottom on both sides
Temperature control accuracy Temperature control accuracy	±1 degree (integrated circuit control, no overshoot)
Furnace temperature uniformity Furnace temperature uniformity	±1 degree (depending on the size of the furnace; larger furnaces can use multi-point control to achieve better furnace temperature uniformity) ±1degree (depending on the size of the furnace, multi-point control can be used in large furnaces to achieve better furnace temperature uniformity)
heating rate	The heating rate is freely adjustable, with the following range: fastest heating rate 40 degrees per minute (non-linear), slowest heating rate 1 degree per hour (non-linear). The heating rate can be freely adjusted, the adjustment

Company Name: Luoyang Ju Xing Kiln Co., Ltd. Company Address:
Advanced Manufacturing Cluster Area, Jianxi District, Luoyang City
Company Address: Jianxi District, Luoyang Advanced Manufacturing Enclave Main website: www.gwdl.com Email:
wqq@gwdl.com Contact information : 13271526781 0379-69936789 Address : No. 1 , Xingye 1st Road, Science and Technology
Industrial Park, Jianxi District, Luoyang City, Henan Province



高新技术企业/专精特新企业
专业的高温加热制造工厂 (-100~2600°C)

中国热处理行业协会理事单位
ISO45001:职业健康管理体系认证
ISO14001:环境管理体系认证
ISO9001:质量管理体系认证
欧盟CE产品认证



咨询电话
13271526781
+86 379-69936789

Contact information: 13271526781, 0379-69936789

Website addresses: www.gwdl.com, www.gwdlcom.cn, www.gwdl.org, www.gwdl.cn